



MUM-14™

Mini-Monocular



The MUM-14 is a high performance modular, hand-held passive night vision monocular device that utilizes a single Generation II/III intensifier tube to provide crisp, clear images under the darkest conditions. The MUM-14 "single tube / single eyepiece" approach to night vision missions is based upon the proven concept that independent use of each eye maximizes the ability of the user to operate under a wide range of low light conditions and maintain maximum situational awareness.

Small and Versatile, the MUM-14 gives you a high performance 2nd or 3rd generation system in the smallest, toughest package available. The MUM-14 has the ability to be weapon mounted, head/helmet mounted, hand-held, optionally attached to cameras and extender 3x/5x Afocal objective lenses. Also available is the dual-system head/helmet mount that allows two MUM-14's to become one binocular system.

Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State, Directorate of Defense Trade Controls as proscribed in the International Traffic in Arms Regulations (ITAR), Title 22 Code of Federal Regulation, Parts 120-130.

DISTRIBUTION: OSR 09-S-2223 Approved for public release; distribution unlimited. © 2019 Nivisys

Feb 15, 2019

FEATURES*

- 2nd/3rd Generation
- High Res: 64 lp/mm
- Lightweight
- Compact
- Rugged Design
- Hands-free Operation
- Integrated IR Illuminator
- Submersible to 20m
- Single Battery Use (AA or CR123)
- MIL-SPEC
- Head, Helmet or Weapon Mountable
- Intuitive Modular Design
- Dual Mini Rails for Fast Head and Weapon Mounting Transition

For more information on the MUM-14 or other Nivisys products call (915) 633-8354 or visit us on the web at www.nivisys.com.

Made in USA

MUM-14[™] BASIC KIT:

- Multi Use Monocular Assembly
- Swing Arm Interface
- Weapon Mount
- Soft Carry Case
- Battery Adapter
- Neck Cord
- Objective Lens Cap
- Sacrificial Filter
- Batteries (AA and CR123)
- Lens Tissue
- Demist Shield
- Shoulder Strap
- Eyecup Assembly
- Operator Manual (not shown)
- Head Mount Assembly with pads



OPTIONS, ACCESSORIES and FEATURES



IR Flood/Spot
Attaches to the unit's IR source



Magnifier Lenses
3x, 4x, 5x Quick attach Afocal lenses



Compass
Attaches to the objective lens



Camera Adapter
Uses a 46mm thread to attach the MUM-14 to a camera for night vision photography. Adapter rings available.



Shuttered Eyecup
For covert operations



Helmet Mount
Easily secures to helmet for combat missions

SPECIFICATIONS*

Image Intensifier Tube
18mm 2nd/3rd Gen

Resolution
1.3 cy/mR (typical Gen III)

Objective Lens
27mm, f/ 1.2

Magnification
1x (unity)

Field of View
40° standard

Focus Range
25cm - ∞

Battery Type
CR123 lithium or AA

Battery Life
>40 hours operations (CR123)
>20 hours operation (AA)

Dimensions (L x W x H)
11.4 x 4.9 x 7.9 cm

Diopter Range
+4 to -6

Weight
298 grams with battery
275 grams without battery

Eye Relief
25mm

Indicators
Low battery (yellow)
IR illuminator (red)

Environmental
-37°C to +54°C (operating)
-51°C to +71°C (storage)
20m (submersible)

*Specifications are subject to change without notice.

